

HI-F TMP-320
HI-F TMP-320
HI-F TMP-320



SPECIFICATION

HOUSING	HIGH GRADE COLD-ROLLED STEEL SHEET FORMED BY HIGH QUALITY MACHINES
SURFACE TREATMENT	ION-PHOSPHATE AND ANTI-RUST FINISHED WITH UV RESISTANT WHITE POLYESTER POWDER COAT
REFLECTOR	PARABOLIC HIGH PURITY ANODIZED ALUMINIUM 99.85% MIRROR FINISH, TOTAL REFLECTION 87% (DIN 5036-3) FROM GERMANY
(OPTIONAL)	WEATHER PROOF GASKET
DIFFUSER	OPAL ACRYLIC (OP), CLEAR ACRYLIC (CL), STIPPLE ACRYLIC (ST), PRISMATIC ACRYLIC (PR)
FRAME	WHITE ENAMEL STEEL FRAME
WIRES	THW, TIS.11-1988 STANDARD
LAMP HOLDER	(HI-F TMP-XXX) ROTOR LOCKED TYPE HIGH-HEAT RESISTANCE, ACCORDING TO TIS344-1987 STANDARD
STARTER HOLDER	ROTOR LOCKED TYPE HIGH-HEAT RESISTANCE, TIS344-1987 STANDARD
PROTECTION CLASS	PROTECTION CLASS EQUIVALENT TO IP 20
INSTALLATION	RECESS T-BAR/M-BAR CEILING, RECESS CONCEAL CEILING
APPLICATION	OFFICE BUILDING, HOSPITAL, DEPARTMENT STORE, UNIVERSITY, GOVERNMENTAL BUILDING, SHOP, ETC.
COMPLETE SET*	INCLUDING BALLAST, LAMP, STARTER NORMAL FOR T8 LAMP

MODEL	LAMP	LUMEN (mm.)	DIMENSION (mm.)			CUT OUT (mm.)		WEIGHT (kg.)	PRICE (Baht.)	COMPLETE SET /*/** (Baht.)
			L	W	H	L	W			
HI-F TMP-320	3 X		595	595	100	580	580	7.00		

