

HI-OW 006
HI-OW 006
HI-OW 006



SPECIFICATION

HOUSING	CORROSION RESISTANT DIE CAST ALUMINUM : STAINLESS STEEL SCREWS
SURFACE TREATMENT	ION-PHOSPHATE AND ANTI-RUST FINISHED WIHT UV RESISTANT POLYESTER POWDER COAT
DIFFUSER	VANDAL RESISTANT TEMPERED GLASS
FRAME	DIE CAST ALUMINUM : SILICONE RUBBER
COLOR	BLACK, WHITE, SILVER
PROTECTION CLASS	PROTECTION CLASS EQUIVALENT TO IP 55
INSTALLATION	WALL MOUNT
APPLICATION	BUILDING, HOTEL, RESTAURANT, RESIDENTIAL, PARKS, WALK WAYS, ETC.

MODEL	DIMENSION (mm.)			LAMP HOLDER	LUMEN (MAX)	LAMP TYPE	PRICE (Baht.)	COMPLETE SET (Baht.)
	L	W	H					
HI-OW 006	120	65	245	1200 cd.	GU 5.3 x 2	MR 16 12V. 50W.	1,600	2,400
HI-OW 006	120	65	245	1200 cd.	GU 5.3 x 2	MR 16 220V. 50W.	1,600	1,800
HI-OW 006/1	160	92	270	1200 cd.	GU 5.3 x 2	MR 16 12V. 50W.	2,000	2,800
HI-OW 006/1	160	92	270	1200 cd.	GU 5.3 x 2	MR 16 220V. 50W.	2,000	2,200
HI-OW 006/1	160	92	270	600 lm.	E 27 x 2	PL 5, 8, 11W.	2,000	2,400
HI-OW 006/2	180	110	300	1000 lm.	E 27 x 2	PL 8, 11, 14W.	2,400	2,800
HI-OW 006/2	180	110	300	6900 lm.	E 27 x 2	PAR 30, 75, 100W.	2,400	3,200
MODEL	DIMENSION(mm.)		LAMP	LUMEN	LAMP			
	Ø	H	HOLDER	(MAX)	TYPE			

