



## GE Area Lighter LED Floodlight

### Product Features

The **Area Lighter** luminaires offer a wide range of optical patterns, color temperatures, lumen packages, and mounting configurations to best optimize area light applications, as well as provide versatility in lighting design within the same form- factor. The Area Lighter offers a lumen range of 10,500 to 33,600 lumens but with better performance and higher efficiency.

# Typical Specification : Area Lighter

## LED & Optical

- **Output Range** : 10500 – 33600lm
- **Photometric Options** : Asymmetrical & Symmetrical
- **IP Rating** : IP66
- **System Efficacy** : 140LPW
- **CCT** : 3000K – 6500K @ 70CRI
- **LED Package** – CREE/LumiLED, Nichia (Upon request)

## Electrical

- **Input voltage** : 90-305 V<sub>AC</sub>
- **Input Frequency** :50/60Hz

## Order Logic:

SKU#	Description	Power (W)	CCT	Lumen Output	Beam Angle	Normal Voltage	Lifetime (Hrs)
70356	ALUASCR75WHSG0	75	5700K	10500	Asymmetrical	90 - 305	50,000
70357	ALUASCR10WHSG0	100	5700K	14000	Asymmetrical	90 - 305	50,000
70358	ALUASCR150WHSG0	150	5700K	21000	Asymmetrical	90 - 305	50,000
70359	ALUASCR200WHSG0	200	5700K	28000	Asymmetrical	90 - 305	50,000
70360	ALUASCR240WHSG0	240	5700K	33600	Asymmetrical	90 - 305	50,000
70361	ALUSCR75WHSG0	75	5700K	10500	Symmetrical	90 - 305	50,000
70362	ALUSCR10WHSG0	100	5700K	14000	Symmetrical	90 - 305	50,000
70363	ALUSCR150WHSG0	150	5700K	21000	Symmetrical	90 - 305	50,000
70364	ALUSCR200WHSG0	200	5700K	28000	Symmetrical	90 - 305	50,000
70365	ALUSCR240WHSG0	240	5700K	33600	Symmetrical	90 - 305	50,000
70367	ALUASN75WHSG0	75	4000K	10500	Asymmetrical	90 - 305	50,000
70368	ALUASN10WHSG0	100	4000K	14000	Asymmetrical	90 - 305	50,000
70369	ALUASN150WHSG0	150	4000K	21000	Asymmetrical	90 - 305	50,000
70371	ALUASN200WHSG0	200	4000K	28000	Asymmetrical	90 - 305	50,000
70372	ALUASN240WHSG0	240	4000K	33600	Asymmetrical	90 - 305	50,000
70373	ALUSN75WHSG0	75	4000K	10500	Symmetrical	90 - 305	50,000
70374	ALUSN10WHSG0	100	4000K	14000	Symmetrical	90 - 305	50,000
70375	ALUSN150WHSG0	150	4000K	21000	Symmetrical	90 - 305	50,000
70376	ALUSN200WHSG0	200	4000K	28000	Symmetrical	90 - 305	50,000
70377	ALUSN240WHSG0	240	4000K	33600	Symmetrical	90 - 305	50,000

## Construction & Finishing

- Die Cast housing with corrosion resistant polyester powder paint, Standard colors: Gray



## Applications

- Open Space Parking
- Tunnel
- Billboard

## Warranty

- **System Warranty** : 5 Year Standard

## Photometric



### Area Lighter

- Asymmetrical

### Area Lighter

- symmetrical

## Product Dimension:

Models	L (mm)	H (mm)	D (mm)
75W/100W/150W	302	373	50
200W/240W	413	373	50

