



TOSHIBA

LED PAR LAMP

Remarkable and unique area by new TOSHIBA LED PAR lamp for indoor using such as Building, Restuarant, Department store and Gallery or use outdoor with weather proof socket fixture for Garden, Tree decoration and outdoor landscape. Comes with various of beam angle in 25 and 35 degree.



PAR20
IP 20




PAR30
IP 65



PAR38
IP 65

DIMENSION



(mm)

EQUIVALENT



Compare to Halogen lamp

ENERGY SAVING



Indoor use only for PAR20



Can use Outdoor for PAR30 and PAR38



RoHS, 1955-2551



Non-DIMMABLE



RoHS Compliant

Product code	Voltage (V)	Rated Wattage (W)	Luminous Flux (lm)	CBCP (cd)	Efficacy (lm/W)	Colour Temperature	Color Rendering Index (Ra)	Beam Angle	IP level	Lifespan (Hrs.)
RLDPC0727WE7TH1	220-240	7	500	1,000	71	2700K	80	25°	20	25,000h
RLDPC0765WE7TH1	220-240	7	550	1,100	79	6500K	80	25°	20	25,000h
RLDPC1027WE7TH1	220-240	10	700	1,500	75	2700K	80	25°	65	25,000h
RLDPC1065WE7TH1	220-240	10	850	1,600	80	6500K	80	25°	65	25,000h
RLDPC1527WE7TH1	220-240	15	1,100	1,900	73	2700K	80	35°	65	25,000h
RLDPC1565WE7TH1	220-240	15	1,200	2,000	80	6500K	80	35°	65	25,000h

Operation temperature : -20°C to 40°C